

## **Specifications**

### **Electrical:**

o Rated Voltage: 250VAC 50/60Hz

o Rated Current: 16A

o Recommended wire size: 2.5mm<sup>2</sup>- 4mm<sup>2</sup>


### **Mechanical:**

o Overall dimension: 88mm x 86mm x 35mm (HxWxD)

Fixing screws centre: 60.3mmBS 4662 wall box compatible

### Standards:

o IEC 60884



Front view



Back view

# Applicable Plugs

Description	Rating	Equivalent Plug Type
2-pin Plug (Non-earth)	2.5A, 250V	A
2-pin Plug (Euro)	2.5A, 250V	С
2-pin Plug Round	10/16A, 250V	E
2-pin Plug (Non-earth)	10/16A, 250V	F
3-pin Plug (BS)	13A, 250V	G
3-pin Plug Round (BS)	5A, 250V	D
2-pin Australia Plug	7.5A, 250V	I (Unearthed)
3-pin Australia Plug	10A, 250V	I
3-pin Australia Plug	15A, 250V	I
3-pin China Plug	6/10A., 250V	I
2-pin China Plug	6/10A., 250V	I (Unearthed)

## Ordering information

Colour	Part No.
White	RCE-KA86S
Silver	RCE-KA86S-4SV
Champagne	RCE-KA86S-4CP
Black	RCE-KA86S-4BL

The information given in this document may be amended. You are also reminded that all products must be installed by a qualified professional.

